





for a long service life

Raised design

 for an easy and quick discharge of the filtercake

High-quality filter plates

for a reliable sealing

Functional connecting fittings

for a rational method of operating



	W.							
VFP 470	Number of chambers	Content (Litres)	Filter area	Overall length (mm)	Overall width (mm)	Overall height (mm)	Infeed height (mm)	Dead weight (kg)
	10	34	3,2	1.685	980	1.480	1.115	750
	20	69	6,5	2.240	980	1.480	1.115	850
	30	104	9,8	2.800	980	1.480	1.115	950
	40	138	13,0	3.360	980	1.480	1.115	1.050
	10	100	10,0	0.000	300	1.400	1.110	1.000
VFP 630	Number of chambers	Content (Litres)	Filter area	Overall length (mm)	Overall width (mm)	Overall height (mm)	Infeed height (mm)	Dead weight (kg)
VFP 630	Number of	Content	Filter area	Overall length	Overall width	Overall height	Infeed height	Dead weight
VFP 630	Number of chambers	Content (Litres)	Filter area	Overall length (mm)	Overall width (mm)	Overall height (mm)	Infeed height (mm)	Dead weight (kg)
VFP 630	Number of chambers	Content (Litres)	Filter area (m²) 11,8	Overall length (mm) 3.200	Overall width (mm)	Overall height (mm) 1.595	Infeed height (mm) 1.170	Dead weight (kg)
VFP 630	Number of chambers	Content (Litres) 131 196	Filter area (m²) 11,8 17,8	Overall length (mm) 3.200 3.700	Overall width (mm) 1.140 1.140	Overall height (mm) 1.595 1.595	Infeed height (mm) 1.170 1.170	Dead weight (kg) 2.100 2.300

Possible special equipment:

Membrane plate with squeezing unit

- for squeezing the filter cake
- for reducing the loss of products

Stainless steel panelling

for a optical upgrading

Drip tight plate version Different feed pumps

Your specialist dealer:



Lochäckerstraße 15 • 75177 Pforzheim

Telephone: 07231 154270 ● Fax: 07231 1542749 ● info@jkf-kuebler.de ● www.jkf-kuebler.de